Technical data sheet - MASSARANDUBA

Brazilian Redwood, also known as Massaranduba, is a gorgeous and durable hardwood whose durability makes it a frequent choice not only for flooring but decking as well. The naturally beautiful heartwood can range from light to dark brownish-red, with a grain that can be straight, somewhat wavy, or interlocked. Brazilian Redwood is also very easy to maintain.

DIMENSIONS

| Brazilian Tropical Species | | |
|----------------------------|-------------------|---------------------------|
| Thickness | Width (mm) | Length (mm) |
| 15MM | 90MM – 120MM | 400 to 1500mm (average |
| | | 900mm) – 100mm increments |
| 19.05MM | 76.2MM - 101.60MM | 400 to 1500mm (average |
| | 127MM | 900mm) – 100mm increments |

We produce other thicknesses and widths on special request with minimum volume being 1 container

GRADING

| Standard European Grade SOLID EXOTIC HARDWOOD PARQUET | | |
|---|----------------------|--|
| Features | Face of the Flooring | |
| Sound Sapwood | Not Permitted | |
| Knots: sound and intergrown | Diameter < 8mm | |
| 3. Knots: unsound | Diameter < 1mm | |
| 4. Checks | Not Permitted | |
| 5. Bark Pockets | Not Permitted | |
| 6. Lighting Shake | Not Permitted | |
| 7. Slope of grain | Permitted | |
| 8. Colour Variation | Permitted | |
| 9. Medullary ray | Permitted | |
| 10. Biodeterioration | Not Permitted | |

Grading Select and Better (detail)





Non visible parts

All features permitted without limit to size or quantity if these do not impair the strength of the wearing quality of the wood parquet.

Quality Control

Grading done piece by piece by experience quality team. (graders and inspectors)



Technical data sheet - MASSARANDUBA

TOLERANCES SOLID EXOTIC HARDWOOD FLOORING

| Structural Tolerances | | | |
|--------------------------|-------------|-------------------------|--|
| Spring | 1 m | Max 0.5 ‰ on <1m length | |
| Cup | | Max 0.7% of the width | |
| Squareness | | Max 0.2% of the width | |
| Tolerances in dimensions | Thickness | +/- 0.2mm | |
| | Width | +/- 0.2mm | |
| | Length | +/- 0.5mm | |
| Moisture Content | Whole Plank | 7-11% MC | |

| Tolerances on Flooring Profile | | | | |
|---|------------------------------|--|--|--|
| Depth of Groove | + 0.3 / - 0mm | | | |
| Width of tongue | + 0 / - 0.4mm | | | |
| Width of groove (t2) thickness of the tongue (t3) | $0.1 \le t2 - t3 \le 0.4$ mm | | | |

PACKAGING

- Pallets with mini-bundles (mini-packs) on each pallet.
- Every mini-bundle (mini-packs) tied up with strong plastic straps.
- Nested lengths per mini-bundle (mini-pack), guaranteeing 900mm average length per mini-pack.





| Packaging Material | | |
|--------------------|--|--|
| Туре | Shrinking Foil around the bundle Thick Foil in the bottom of the bundle (blue) | |
| Material | Plastic | |
| Thickness (mm) | 0.09 | |
| Edge Protection | Cardboard on every edge for protection | |