










	Profile	Wood species	Surface finish	Dimensions			Description
				mm (T)	mm (W)	m (L)	supporting material
FLOOR SKIRTINGS	Floor skirtings with wooden veneer						
	 19x40mm	ASH	oil	19	40	2,40	plywood
		DOUSSE	oil	19	40		
		BEECH	oil	19	40		
		OAK	oil	19	40		
		WALNUT	oil	19	40		
		MERBAU	oil	19	40		
		OAK	white	19	40		
			ebony	19	40		
	 13x50mm	OAK	without SF	13	50		
			transparent	13	50		
			white	13	50		
			smoked	13	50		
			naturel	13	50		
			grafit	13	50		
 5/7x35mm	OAK	without SF	5	35			
		oil					
	TEAK	without SF	7	35	pine		
Solid wooden skirting boards							
	Pine without knots	without SF	20	42	2,70	solid	
	Knotty larch	without SF					
	Knotty larch	oil					
	OAK	without SF	18	50	2,00	solid	
	OAK	without SF	7	35	2,40	solid	
	ASH						
	TEAK						
	PALISANDER						
Solid floor profiles							
OAK PROFILES	Profile	Wood species	Surface finish	Dimensions			Description
				mm (W)	mm (T)	m (L)	Supporting material
	BALANCING	OAK	OSMO oil	40	20	1,5-2,40	solid OAK
	TRANSITIONAL			40	20		
	TERMINATING			34	20		
STAIRCASE	20			40			

PRIMERS AND SQUEEGEES		Primer - for absorbent and non-absorbent substrates	10kg	OKATMOS EG20	1	does not contain solvents, excellent adhesion, can be used on old adhesive layers
		Primer - under BAKIT adhesives	5kg	BAKIT PV Universal	1	dispersion primer for good adhesion of all dispersion and resin parquets adhesives
		Self-leveling trowel - for alignment 2-20mm	25kg	SERVOFIX F210	1	universal putty compound for cement base with additive polymers
		Self-leveling trowel - for alignment up to 1-30mm	25kg	SERVOPLAN P200 PLUS/ SERVOPLAN Ki 1	1	with an additive of polymers suitable for leveling substrates under wooden floors and parquet
		Repair quick-drying squeegee	25kg	SERVOPLAN R300S a Ki300	1	suitable for settlement steps, holes, landings and larger irregularities at any time thickness screed layers.
Self-leveling trowel - with elastic fiber up to 3-15 mm	20kg	SERVOPLAN S444	1	quick-drying trowel fiber reinforced, high ultimate strength and very good spilling capabilities, suitable for wooden substrates (planks, plates,...)		
ADHESIVE full surface bonding		Adhesive for parquet and laminate - flexible elastic adhesive	17kg	BAKIT EK	1	Suitable for parquets, mosaics, multilayer floors and solid wood above 60 cm, on cement and anhydride screeds, vertical wood chips V100,...
		Adhesive for multilayer floors - elastic adhesive	17kg	BAKIT FPK	1	Suitable for multi-layer floors, also suitable for longitudinal heating, and oak treated with ammonia
		Parquet adhesive - 2 component polyurethane adhesive	10 kg (component A+B)	BAKIT PU-P	1	like Bakit FPK, plus suitable for exotic trees